

Index

Note: Page numbers with “f” denote figures; “t” tables.

A

Agitation
 defined, 345
 jacket vessels, 126
Agitators, helical pipe coils with, 332
Air hardening, 738
AISC *Steel Construction Manual*, 186, 188
Allowable stresses and load combinations,
 200–201
Alloys, 720–721
Anchor bolts
 conical skirt, 252
 saddle supports for large vessels, 271–272
 for vertical vessels, 293
Anchor bolts, base details and
 centered neutral axis method, 291–292
 equivalent area method, 191
 force, 291
 number of, 283t, 291
 shifted neutral axis method, 283t, 284, 288
Anchor strap, 430

Anchoring of saddle supports, 187–188
Anchor-type impellers, 346
Angle α , calculating, 67
Angle joint, 762
Annealing, 738–740
ASCE, wind design per, 189–197
ASCE/SEI 7-10, 190
ASME (American Society of Mechanical
 Engineers)
 Section VIII, Division 1, 2–4, 6–7, 10–11,
 13, 15–16, 27, 29, 55–56, 83, 85–86,
 136, 186, 200–201, 428, 474, 481,
 496–497, 509, 594, 744–745
 Section VIII, Division 2, 2, 5–8, 10–11, 13,
 15–21, 27, 56–57, 95–96, 146, 186, 188,
 200–201, 474–476, 481, 496–497, 499,
 509, 594, 733
 Section VIII, Division 3, 21, 475–476,
 481, 497, 499
 specifications, 737–738
 STS-1 method, 420–421, 425

Attachments, converting, 399–401
Autoclave testing, 740
Autofrettage, 482–483
 history of, 483
 pressure, 483
AWWA D-100, 588, 594
Axial compression
 buckling of thin wall cylindrical shells,
 95–96
Axial stress, 80
Axle loads, 573

B

Baffles
 applications, 381–390
 attaching stiffeners, do's and don't's for,
 384
 configurations, 390
 curved, 381
 dimensions, 382
 helical pipe coils with, 332

- Baffles** (*Continued*)
 for mixers/agitators, 347–348
 notation, 382
 sample problem, 386–388
 stiffened versus unstiffened, 381
 stiffener design, 384
 thermal check, 384
 unstiffened, check, 384
 weld sizes, 385–386
 widths and wall clearances, 345
- Bar stiffeners**, moment of inertia of, 49t
- Barge transportation** *see* Transportation, barge
- Base details for vertical vessels**, design of
 anchor bolts, equivalent area method, 286f, 287f
 anchor bolts, force, 291–292
 anchor bolts, number of, 283t, 291
 base plate, 288f, 292
 bending moment, 284t
 bolt chair data, 283t
 bolt stress, allowable, 283t
 concrete properties, 284t
 constants, 284t
 gussets, 289–290
 notation, 281–282, 291
 skirt thickness, 290
 skirt types, 282f
 stresses, allowable, 291–292
 top plate or ring, 289
- Base plate designs**, 681–690
 for legs, 275–276
 for lugs, 281t, 700
 for saddles, 270–271
 weights of, 112t
- Base plate designs**
 conical skirt, 252
- Base support damping**, 419
- Bauschinger Effect**, 483
- Beam on elastic foundation methods**, 436
- Beams**
 beam seat, 298, 305f
 multiple loads, 575
 support blocks welded to, 319–320
 tail, 681–690
see also Support of internal beds
- Bending moment**, 80
 buckling of thin wall cylindrical shells, 96
- Bending stress**
 primary general, 11, 80
 secondary, 12
- Biaxial states of stress**, 4
- Bijlaard, P. P.**, 188
 analysis, 436, 448
- Bins**
 compression ring design, 590–591
 deep, granular/powder, 589–590
 deep versus shallow, 587
 dimensional data, 587f
 material properties, 593t
 notation, 586
 purging techniques, effects of, 594
 rankine factors, 593t, 594
 roofs, 594
 shallow, granular/powder, 588–589
 small internal pressures, 590
 solids versus liquids in, 586
 struts, 591
 support arrangements, 593
 surcharge, 594
 weights, 586–587
- Blind flanges with openings**, 167
- Bolt(s/ing)**, 593
 application, 729t
 check of, 701
 flange, 72, 147t, 148, 163t, 164f, 696t, 701
 loads for rectangular, 699
 materials, 728, 729t
 properties, 696t
 weights of alloy stud, 111t
- Bolt spacing**
 maximum, 144
 minimum, 144
- Bolt torque**, for sealing flanges, 169–171
 calculations, 171
 friction factor, 170
 gasket material, modulus of elasticity of, 170
 notation, 169–170
 notes, 171
- Bolted connections**, shear loads in, 584–585
 bearing type connection, 585
 cases of, 584–585
 friction type connection, 585
- Bolted flange connections**, bolt loads in, 141
- Bolted flat covers**, 508–509, 510f
- Bottom catalyst dump nozzles**, dimensions/weights of, 115f
- Braces**, leg, 187
see also Legs, seismic design for braced
- Brackets**
 cantilever-type, 580
 circular platforms and spacing of, 570
 high-temperature, 579
 types of, 576
- Bridgman closure**, 504, 518–537
 calculation procedure, 528–537
 design procedure, 523
 nomenclature, 523
 studding flanges, worksheet for, 527f, 538f
 threaded closures with, 539–545
- Brinell testing**, 735–736
- Brittle fractures**, 8
- Buckling**
 creep, 29
 elastic, 56
 general, 29
 lateral, of stiffening rings, 51–52
 local, 29
- Buckling of thin-walled cylindrical shells**, 95–96
 axial compression, 95–96
 bending moment, 96
 critical length, load, and stress, 95
 external pressure, 95
 interaction, 96
 shear stress, 96
- Buildings**
 risk category of, for wind and earthquake loads, 207
- Buried vessels**, *see* Underground tanks and vessels
- Butt joint**, 762
- C**
- Carbide solution treated**, 763
- Carbon steel plate**, weights of, 101
- Centered neutral axis method**, 282, 291–292
- Center of gravity**, finding or revising, 90
- Charpy impact testing (CIT)**, 736–737
- Choker (cinch) lift at base**, 688
- Circular platforms**
 bracket spacing, 570
 dead loads, 570
 dimensions, 563f, 564f
 formulas, 564
 kneebrace design, 565, 570
 live loads, 567t, 568t, 570
 moment at shell graph, 566f
 notation, 563–570
- Circular rings**, stress in
 allowable stress, 438–439
 coefficient graphs, 445f
 coefficient values, 438t, 439t
 moment diagrams, 437f
 moments and forces, determining, 439
 notation, 437
 radial load, determining, 437
 shell stress due to loadings, 439t
- Circumferential compression stress**
 torispherical head, knuckle region of, 72f
- Circumferential/latitudinal stress**, 3
 formula, 38
- Clips**, 575
- Closures**, 502–547
 Bridgman, 504, 518–537
 delta ring, 504, 515–517
 double cone, 513

- flanged, 503
 - lens ring, 511
 - see also* High pressure closures
 - Code Case 2286, 54–57, 56t
 - nomenclature, 54–57
 - Coil wrapped thick-walled pressure vessel, 476
 - Coils *see* Helical pipe coils
 - Collapse, use of term, 12
 - Columns *see* Leg supports
 - Composite stiffeners
 - baffles and, 381
 - moment of inertia of, 50t
 - Compression plate, 280–281
 - Compression ring design, bins and elevated tanks and, 590–591
 - Concentric cone, 59f
 - Concrete, properties of, 295
 - Cone lifting lugs, 691–693
 - Cones, formula, 39t
 - Cone-cylinder intersections, 64
 - dimensions of, 59f
 - worksheet to determining loads at, 65f, 66f
 - Cones, design of, 58–64
 - for external pressure, 61–63
 - geometry, 59
 - with half apex angle, 63
 - for internal pressure, 59–60
 - nomenclature, 58
 - notes, 64
 - sample problem, 64
 - Conical skirt, seismic design for, 248–252
 - anchor bolts, 252
 - base plate, 252
 - calculation, 251
 - design of, 251
 - longitudinal stress in shell due to shear band, 252
 - nomenclature, 248
 - notes, 252
 - shear ring, 251
 - Conventional jackets, 124
 - Conversion factors, 357
 - Corner joint, 762
 - Corrosion
 - fatigue, 8
 - stress, 8
 - Creep, 23–31
 - allowable tensile stress in, 26–27
 - allowable compressible stress in, 27
 - buckling, 29
 - fatigue, 27–29
 - stages of, 24–25
 - Creep-buckling, 29
 - Creep-fatigue, 27–29
 - Critical length, 95
 - Critical Reynolds number, 126–127
 - Critical wind velocity, 418, 420, 423f
 - Cross bracing, 187, 218–222, 615
 - Cryogenic applications, 32–33
 - specifications, 33
 - Cut threads, 763
 - Cycle counting methods, 16
 - Cyclic service, fatigue analysis for, 15–23
 - cycle counting methods, 16
 - factors influencing design, 15–16
 - general, 21
 - histograms, 16
 - protection against ratcheting, 21
 - screening procedures, 16–21
 - Cylinders
 - calculating proportions, 99t
 - see also* Cone-cylinder intersections
 - Cylindrical shells, 38
 - buckling of thin-walled, 95–96
 - external pressure design for, 43
 - formulas, 38
 - Cylindrical shells, stress in
 - bending moment, 458f, 460f, 462f
 - calculating β values for rectangular attachments, 452–454
 - calculation steps, 452–454
 - circumferential moment, 454, 455t
 - concentration factors, 450f
 - dimensions for clips and attachments, 450f
 - geometric parameters, 451f
 - longitudinal moment, 453, 455t
 - membrane force, 457f, 458f, 461f
 - notation, 449–464
 - radial load, 452
 - shear stress, 456
- D**
- Damping
 - β values, 421t
 - coefficient and topographic factors, 422t
 - data, 423–424
 - design criteria, 419–420
 - design modifications, 420
 - equations, 424
 - factor, 419
 - graph of critical wind velocity, 423f
 - precautions, 420
 - procedures and examples, 424–425
 - summary of, 421t
 - types of, 419
 - Data sheet, sample, 745
 - Davits
 - arrangement, 562f
 - moments and forces, 558–559
 - notation, 558–563
 - radial load, 560–561
 - selection guide, 559f
 - stress in, 559–560, 563
 - types of rigging, 558f
 - Dean effect, 126, 327
 - Defect evaluation, minor, 780
 - Defects and failures of pressure vessels, 733
 - Deflection
 - dynamic, 420
 - static, 420
 - tower, 399–401
 - Dehydrogenation heat treatment (DHT), 740
 - Delta ring closure, 504, 515–517
 - Demisters, 376
 - configuration of, 377f
 - flow distribution, guidelines for maintaining, 378f
 - notes, 376
 - pads, properties of, 380t
 - Density of various materials, 112t
 - Design
 - failure, 7–8
 - load combinations, 34t
 - pressure, 83, 762
 - temperature, maximum, 84
 - Dimpled jackets, 125
 - Discontinuity stress, 14
 - Dished heads *see* Torispherical heads
 - Displacement method, 14
 - Distortion energy theory, 5, 7
 - Distribution forging, 551, 552f
 - Double cone closures, 513
 - Double eddy, 126, 327
 - Downcomer bars, weights of, 109t
 - Draining vessels, time required for, 777–778
 - Drums
 - calculating L/D ratio, 96
 - sizing of, 96
 - types of, 96
 - Dynamic analysis, 200, 420, 425
 - Dynamic deflection, 420
 - Dynamic instability, 418
 - Dynatech test, 410
- E**
- Eccentric cone, 58f
 - Elastic deformation, 8
 - Elastic-plastic method, 21
 - Elastic ratcheting analysis, 21
 - Elastic stress analysis, 21
 - Elasticity, modulus of, 170, 170t
 - Elastomeric O-Rings, 508
 - Ellipsoidal heads
 - internal pressure and, 70–75
 - proportions, calculating, 99
 - Elliptical, internal manways, 181

- Elliptical heads, reinforcement for openings
in, 85
- Elliptical openings, reinforcement for, 85
- Empty weight, 102
- End plug, 509, 518, 532, 539
- Energy absorbed by shell, 419
- Equicohesive temperature, 24
- Equivalent lateral force (ELF), 200
- Erection
bolting, 593
contractor duties, 586–587
design steps, 664
flanges, top body, 672
grouting, 594
guidelines, 660
leveling, 591
lifting attachments, types of, 666–674
lifting loads and forces, 675–680
local loads in shell due to, 710–712
lugs, dimensions and forces of, 674f
lugs, shell flange, 672
notation, 665
plumbness, 591
requirement for, 586
shims, 590–591
soleplates, 590
straightness, 591
stresses, allowable, 664–665
tailing devices, 660
tolerances, 589–590
trunnions, 672
vertical vessels, setting of, 586
weight, 102
- Euler, 29
- Examination of pressure vessels, 732
- External pressure
buckling of thin wall cylindrical shells, 95
Code Case, 2286, 56, 95
for external pressure, 44f, 61
for cylindrical shells, 43
dimensional data for cones due to, 69f
for intermediate heads, 74f
jacket vessels, 125
openings and, 86
for spheres and heads, 45f, 47–48
stiffeners, combining vacuum with other
types, 42
stiffeners, location of, 169–170
stiffeners, moment of inertia of bar, 49t
stiffeners, moment of inertia of composite,
50t
stiffening rings, check for external
pressure, 75f
stiffening rings, moment of inertia of, 50
toriconical transition, 69, 70
unstiffened shells, maximum length of,
48t
- External restraint, 13
- External ring stiffener, 52
sample problem given, 53
- F**
- Fabricated weight, 102
- Fabrication failure, 3–7
- Failures, 7–8
categories of, 7–8
failure modes, 8
- Fatigue
analysis, 15–23
creep, 27–29
screening criteria for, 10t
- Fatigue, analysis, for cyclic service, 15–23
cycle counting methods, 16
factors influencing design, 15–16
general, 21
histograms, 16
protection against ratcheting, 21
screening procedures, 16–21
- Fiber elongations, 134–137
- Fillet weld, 782
- Finite element analysis, 436
- Flange(s)
blind flanges with openings, 167
dimensions, for RTJ gasket, 145f
flat face, dimensions of, 144
flat face, 155f
full gasket, 155f
maximum allowable pressure for, 164f
reverse, 154f
ring, 153f
slip-on, 152f, 155f
standards, 140
studding, 176–177, 178f
weld neck, 151f
- Flange design, 139–184
notes, 144–148
strategy, 140–141
- Flanged closures, 503
- Flanged heads *see* Torispherical heads
- Flanges
blind, with openings, 167
bolt hole orientation, 798
bolt torque for sealing, 169–171
bolts, 147t, 163t
coefficients, table of, 158t–160t
erection utilizing top body, 672
formulas, 11
gasket facing and selection, 141–142
gasket materials and contact facings,
34t
gasket widths, 34t
high-pressure, 140
hub stress correction factor, 162f
- integral factors, 25f
loose hub factors, 27f, 28f
low-pressure, 140
maximum allowable pressure for, 77f
notation, 11
reverse design, 77f
RFWN, 113f
ring design, 76f
slip-on (flat face, full gasket) design, 77f
slip-on (loose) design, 75f
special, 140–141
steps for designing, 140–141
studded, 517, 549f, 550f
weights of, 106t
weld neck (integral) design, 74f, 104f
see also Lugs, flange
- Flat face flange, 155f
- Flat heads, 76–80
examples, 76–80
formulas, 76
large openings in, 81–83
notation, 76
openings in, 85
stress in, 80
- Flat plates, 775–776
- Flat ring gaskets, 504
- Follower ring, 529
- Force method, 14
- Forming strains, 134–137
- Formulas
for calculating weights, 104f
for cylinders, 38
dimensional, 68
flanges, designing, 11
flat heads, designing, 76
general vessel, 38, 764–767
minimum design metal temperature,
91–92
stress factors, 81, 150
torispherical and ellipsoidal head, for
stress, 71f
- Fracture appearance transition temperature
(FATT), 763
- Friction factor, 170
- Full anneal, 740
- Full gasket flange, 155f
- G**
- Gaskets, 507–508
allowable pressures, 509t
Bridgman, 503–505, 507
contact faces, types of, 143
contact surface finishes, 143–144
delta ring, 503, 504, 507, 515–518, 518f
double cone, 503, 505, 513–515, 513f–
515f
effective width, 157t

- facing and selection, 141–142, 143t
 factor, 141
 flat ring, 504
 lens ring, 503, 505, 511, 511f, 512f
 material, modulus of elasticity of, 170
 materials and contact facings, 156t
 metal, 507–508, 507t
 O-ring, 503, 505, 508
 ring joint, 504
 RTJ gasket, flange dimensions for, 145f
 self energized, 505
 self sealing closures with non-yielding, 505
 self sealing closures with yielding, 504
 self-energized, 505, 508
 types of, 142t
 widths, 157t
 yielding, 503, 504
- General buckling, 29
 General loads, 9
 Geometry factors, 81
 Girder, 614
 column design, properties of, 614–615
 combined section, properties of, 614
 compression case, 615
 stiffeners, properties of, 614
 tension case, 615
- Gravity separation, 376
 Gross structural discontinuity, 762
 Grouting, 594
 Gussets, 278–279, 289–290
 designing, 326–327
- H**
- Handling operations, 713f
 Hardness testing, 734–735
 requirements for, 735
 Rockwell, 736
 Vickers pyramid, 736
- Heads
 external pressure design for hemispherical, 42–50
 flat, 76–83
 formula, 39t
 intermediate, 74–75
 internal pressure and ellipsoidal, 76
 internal pressure and torispherical, 76
 properties of, 748
 stresses in, due to internal pressure, 70–73
- Heads shape, tolerances for, 792
 Heat transfer coefficient, 126, 327, 339t, 340t
 Heat treatment, 738–741
 defined, 740
 terms and conditions of, 738–741
 types of, 739f
- Helical pipe coils, 326–344
 advantages of, 326
 baffles and agitators, 332
 calculations, 333–335
 data, 336t
 design requirements, 326–327
 design tips, 326–327
 examples, 319–327
 film coefficients, 336t
 gases, properties of, 336t
 heat loss, 339t
 heat transfer coefficient, 327, 339t, 340t
 layout for flat-bottom tanks, 330f
 liquids, properties of, 338t
 manufacturing methods, 326
 metal conductivity, effect of, 344t
 metals, thermal conductivity of, 337t
 notation, 332
 notes, 327–330
 physical design, 326
 pressure drop, 327, 335
 Reynolds number, 336, 339, 352–353
 steam and water, properties of, 337t
 steam and water, viscosity of, 338t
 supports for, 331
 thermal design, 326
 types of, 329f
 water and liquid petroleum products, viscosity of, 343f
- Hemispherical heads, external pressure and, 45f, 47–48
- High pressure closures, 503, 506t
 design methods, 505
 flanged, 503–505
 flat ring gaskets, 504
 materials, 504
 ring joint gaskets, 504
 self energized gaskets, 505
 self sealing closures with non-yielding gaskets, 505
 self sealing closures with yielding gaskets, 504
- High pressure vessel, 473–556
 ASME VIII, Division 3, 475–476
 construction types, 476, 478f
 design options checklist, 484t
 examples, 487
 general, 474–487
 multilayer, 480–482
 testing & NDE requirements, checklist of, 485f, 486f
see also Shell design
- Hilicoflex O-Rings, 508
 Histograms, 16
 Holding times, 779f
 Homogenization, 740
- Horizontal vessels
 erection of, 669f
 partial volumes of, 752f, 753t
 platform splice, 573
 platforms for, 572f
 tolerances for, 784f, 785–786
 walkways or continuous platforms for, 573
see also Saddles, horizontal vessels and design of
- Hot box design, 186
 Hot wire method, 410
 Hub rings
 for bed supports, 321
 bolted splice connection, 323f
 defined, 321
 gussets, designing, 321–325
 load design for, 325f
 loads and dimensions of, 323f
 nomenclature, 321
 with radial beams, 321, 322f, 324f
 ring analysis, 315
 splice connection, designing, 323–325
 support ring, 321
 supports for, 325f
 torsion in, 326
- Hydraulic pre-tightening, 547
 Hydrostatic end forces, 82
 Hydrostatic testing of pressure vessels, 733–734
 field, 734
 shop, 733
- I**
- Impact testing, avoiding, 91
 Impellers
 action of, 351
 types of, 346, 349
 Impingement plates, 391
 calculation, 391
 nomenclature, 391
 Incremental collapse, 8
 Intercrystalline, 24
 Intermediate heads
 external pressure and head thickness, 74
 internal pressure and head thickness, 74
 methods of attachment, 75f
 shear stress, 75
 Intermediate stress relieve (ISR), 740–741
 Internal force, 80
 Internal pipe distributors, 353–357
 calculations, 356
 descriptions, 360f
 dimensions for, 355f
 examples, 356–357
 feed options (elevations), 358f, 359f

- Internal pipe distributors (*Continued*)
 nomenclature, 354–356
 notes, 354
 sparger details, 361f
- Internal pressure
 buckling and, 96
 cone for internal pressure, 59–60
 for ellipsoidal heads, 70–73
 for intermediate heads, 74
 for torispherical heads, 70–73
- Internal restraint, 13
- Internal ring stiffener, 53
 sample problem given, 54
- Interrupted Quench, 740
- Isochronous curves, 29
- J**
- J factor, 741
- Jack bolts, 518, 529–530
- Jacketed vessels, 124–127
 agitation, 126
 closures, types of, 131f, 132f
 conventional, 124
 critical Reynolds number, 126–127
 design, 125
 dimpled, 125
 equivalent diameter, finding, 125–126
 external pressure, 125
 heat transfer coefficient, 126
 miscellaneous details, 130f
 multi-jacketed vessels, external piping
 configurations for, 129f
 nomenclature, 127
 pressure drop, 125–133
 sample problems, 127–133
 with spiral baffle, 124
 spiral half pipe coil welded to shell,
 124–125
 spiral pipe coil welded to shell, 124
 thermal design, 127–133
 thickness of, 127–133
 types of, 128f
- K**
- Kneebraced design
 pipe supports, 578, 581
- Knuckle radius, thickness required, 69–70
- L**
- L/D ratio, 96
- Lame' equations, 499–502
- Large diameter, self-reinforced manways,
 dimensions and weights for, 116f
- Large-diameter nozzle openings, 394
- Larson-Miller relation, 26
- Lateral buckling, of stiffening rings,
 51–52
- Lateral stability, 299
- Lattice beams, 310–315
 configuration of, 310f
 design of, 313f
 diagonals of, 314
 dimensions of, 310f
 end diagonal of, 314–315
 load design for, 312f
 notes, 315
 properties of, 314
 ring analysis, 315
 stability check, 315
- Leg supports, 187
 base plates for, 275–276
- Legs, erection of vessels with, 669f
- Legs, seismic design for braced
 flow chart for, 216f
 legs and cross-bracing, sizes for, 223
 load diagrams, 218f
 notation, 217
- Legs, seismic design for unbraced
 calculations, 210
 dimensional data, 209f
 leg configurations, 209f
 leg sizing chart, 214f
 notation, 208–209
 vertical load, 213t
- Length, critical, 95
- Lens ring closure, 511
- Lifting *see* Erection
- Ligaments, 86
- Lightly loaded attachments, 762
- Linear elastic, 497
- Loads
 combinations, 10t, 200–201, 643
 lifting, 675–680
 on wire rope, 714f
- Local buckling
 defined, 29
- Local loads, 8–9
 attachments, converting, 448
 methods for analyzing, 436
 methods for reducing shell stress,
 436–437
 ring stiffeners, partial, 446–448
 in shell due to erection forces, 710–712
 stress in circular rings, 446
 stress in cylindrical shells, 449–464
 stress in spherical shells, 465–471
- Local primary membrane stress, 12
- Local thin area (LTA), 432–433
 multiple, 433
 nomenclature, 432
 notes, 433
 single, 432–433
- Logarithmic decrement, 420, 421t
- Longitudinal/meridional stress, 3
- Lubricating bolts, 171
 formula, 39t
- Lugs, 188
 dimensions and forces, 674f
 shell flange, 672
 side, 670f, 671f
 tailing, 689–690
 top head and cone lifting, 691–693
- Lugs, design of
 base plate, 275–276
 compression plate, 280–281
 dimensions, standard, 281t
 gussets, 278–279
 notation, 278
- Lugs, flange
 base plate design, 700
 bolt loads for rectangular, 699
 bolt properties, 696t
 bolts, check of, 701
 design steps, 698
 diagram, 695–704
 dimensions, 696t
 full circular base plate design, 699
 loads, 674
 nozzle flange check, 698
 sample problem for top, 702–704
 side, 697, 711–712
 tension, maximum, 698
 top, 697, 711–712
- Lugs, seismic design for, 229–239
 anchor bolts required, size of, 238
 β values, computing equivalent, 233t,
 453
 coefficients, 453t
 geometric parameters, computing, 233
 notation, 223–230
 radial loads, 233f, 234t, 235f
 radial thermal expansion, 238
 reinforcing pads, use of, 233–234
 stress diagrams, 254f
 stresses, 234t, 455t
 stresses, combining, 234f
 stresses, computing, 232f
- M**
- Magnetic particle inspection, 737
- Main nut, 518, 539
- Major attachments, 762
- Manways, weights of, 108t
- Material
 failure, 7–8
 properties, 59t
 selection guide, 61t
- Maximum allowable nozzle loads, 462–464
- Maximum allowable pressure (MAP), 762
 calculating, 53
 defined, 83

- Maximum allowable temperature (MAT), 762
- Maximum allowable working pressure (MAWP), 762
calculating, 53
defined, 83
- Maximum permissible bow, 787
- Maximum principal stress theory, 4, 7
- Maximum shear stress theory, 4–5
- Maximum stress theory, 4f
- Max-min cycle counting procedure, for fatigue analysis, 16
- Mechanical pre-tightening, 547
- Membrane stress
analysis, 3
local primary, 12
primary general, 12
secondary, 12
- Mesh pad construction and installation, 379f
- Metal gaskets, 507–508
properties of, 507t
- Metal O-Rings, 508
- Metric guidelines and conversions, 768–771
- Minimum design metal temperature (MDMT), 763
arbitrary, 91
design temperature and, 84
determining, 91t
exemption, 91
flow chart for, 94f
formulas, 91–92
notation, 90–91
test, 91
- Minimum pressurization temperature (MPT), 763
- Minor attachments, 762
- Minor defect evaluation, 12
- Mist eliminators, *see* Demisters
- Mixers
applications, 345, 350f
baffles, 345, 348
impellers, action of, 351
impellers, types of, 346, 349
mounting, 345, 348
notation, 345–351
- Mixing, defined, 345
- Modal response spectrum analysis, 200
- Moment coefficients for base rings, 686t
- Moment of inertia
of bar stiffeners, 49t
calculation form, 398f
of composite stiffeners, 50t
of stiffening rings, 50f
- Moments, calculating, 82
- MPC Omega method, 26
- Multi-jacketed vessels, external piping configurations for, 129f
- Multilayer autofrettage thick-walled pressure vessel, 9
- Multilayer pressure vessels, 480–482
advantages of, 481–482
in ASME Code, 481
disadvantages of, 482
features of, 481–482
general, 481
history of, 480
- Multilayer thick-walled pressure vessel, 476
- Multiwall thick-walled pressure vessel, 476
- N**
- National Building Code (NBC), 425
- Nil ductility transition temperature (NDT), 763
- Normal loads, 9–10
- Normalizing, 740
- Norton-Bailey power law, 26
- Nozzle position, 89f
- Nozzle reinforcement, 85–86
for large-diameter openings, 394
- Nozzles, 551
bottom catalyst dump, 115f
quench, 114f
side catalyst dump, 119f
through, 181
weights of, 108t
- O**
- Obround openings, reinforcement for, 85
- Occasional loads, 9–10
- Openings
in elliptical heads, 85
external pressure and, 86
in flat heads, 81–83, 85
large-diameter nozzle, 394
multiple, 86
near seams, 86
through seams, 86
in torispherical heads, 85
- Operating pressure, 84
- Operating temperature, 84
- Operating weight, 102, 267
- O-Rings, 505, 508
elastomeric, 508
hilicoflex, 508
metal, 508
- Overstrain ratio, 483
- Over-tightening, 547
- Overweight percentage, 102
- P**
- Paddle-type impellers, 346
- Panel test, 410
- Partial ring stiffeners, 446–448
- Peak stress, 12–13
- Perforated spargers *see* Internal pipe distributors
- Period of vibration (POV), 201–204, 202f, 203f, 206f
- Pipe coils *see* Helical pipe coils
- Pipe distributors, 353
- Pipe supports
alternate-type, 581
brackets, cantilever-type, 580
brackets, high-temperature, 579
brackets, types of, 576
design of, 576–583
dimensions, 576t
kneebraced, 578, 581
unbraced, 576
weight of, 577t
- Pipes, weights of, 110t
- Plastic deformation, excessive, 8
- Plastic instability, 8
- Plate overage, 102
- Pneumatic testing of pressure vessels, 734
- Post connection plate, 616
- Posts *see* Leg supports
- Precipitation hardening, 763
- Pressure drop, 125–126
jacket vessels, 125–133
- Pressure
design, 83
drop and design of helical pipe coils, 125–126, 335
operating, 84
see also External pressure; Internal pressure
- Pressure relief values (PRV's) application, guideline for, 801
- Primary stress
bending, 80
general, 11
local, 12
- Process Anneal, 740
- Proof testing of pressure vessels, 734
- Propeller-type impellers, 346
- Pull-up studs, 528–529
- PWHT
maximum, 741
minimum, 741
requirements for, 21–31
- Q**
- Quench & tempered, 763
- Quench nozzles, weights of, 114f
- Quenching, 740

R

Radial beams
 hub rings with, 322f, 324f
 load design for, 325f
 moment of inertia of, 319

Radial stress, 3

Radial thermal expansion
 seismic design for lugs, 238

Radiographic examination, 738

Rail transportation *see* Transportation, rail

Rainfall cycle counting procedure, for
 fatigue analysis, 16

Rankine factors, 593t, 594

Ratcheting, 21

Reactor bottom outlet estimated weights,
 118f

Reactor inlet estimated weights, 117f

Recrystallization, 740

Rectangular platforms, 571–575

Refractory lined equipment, 411

Refractory lined vessels, 411

Refractory lines components, skin
 temperature of, 412

Refractory linings
 allowable refractory stresses, 408
 calculations, 415–416
 creep rate, 408
 failures and hot spots, causes of,
 410–411
 flow chart, 413f
 heat loss and cold face temperature,
 calculating, 409–410
 hot versus cold face, 408
 notation, 299, 397, 414
 notes, 411–412
 properties and data, 397
 properties of materials, 417t
 selection, 408–409
 shrinkage, 408
 spalling, 408
 specific heat, 410
 stresses, allowable, 394
 summary of results, 418t
 thermal conductivity, 410

Refractory materials, properties of, 417t

Reinforcement
 nozzle, 85–86, 394
 for studding outlets, 175

Relaxation of joints, 171

Reservoir cycle counting procedure, for
 fatigue analysis, 16

Resistance, 419

Retaining ring, 530–531

Reverse flange design, 154f

Reynolds number, 126, 334, 369f

Ribbon wound, 479f, 480

Rigging, terminology, 558f

Ring(s)

analysis, 436–446
 compression, 590–591
 joint gaskets, 504
 support of internal beads, 306
 supports, 189
see also Circular rings, stress in;
 Hub rings; Stiffening rings

Ring flange design, 153f

Ring girders
 bending moments, internal, 403t
 design check for base, 683
 design steps, 404–406
 dimensions and forces, 402f
 formulas, 403
 load diagrams, 404
 notation, 402–403

Rings, seismic design for
 calculations, 224
 coefficients, 226f
 maximum bending moments, 228t
 notation, 223–229
 thickness, determining, 241f

Roark Technical Note, 446

Rockwell hardness testing, 736

Rolled threads, 763

S

Saddle(s)
 supports, 187–188
 weights of, 112t
see also Transportation, shipping saddles

Saddles, horizontal vessels and design of
 circumferential bending, 262
 circumferential compression, 262
 coefficients, 263f, 264t
 dimensional data, 254f
 dimensions for saddles, 265f
 longitudinal bending, 261–262
 moment diagram, 255f
 notation, 253–254
 procedure for locating, 260
 stress diagram, 223
 stresses, shell, 260
 stresses, types and allowable, 259–260
 tangential shear, 262
 transverse load, 257

Saddles, large vessels and design of
 anchor bolts, 271–272
 base plate designs, 270–271
 dimensional data, 268f
 forces and loads, 267–269
 notation, 267
 rib design, 272–273
 web design, 269

Sealing flanges, bolt torque for, 169–171
 calculations, 171

friction factor, 170
 gasket material, modulus of elasticity of,
 170
 notation, 169–170
 notes, 171

Seams
 openings near, 86
 openings through, 86
 pads over, 86

Secondary stress, 12

Seismic design, general, 199–204
 allowable stresses and load combinations,
 200–201
 equivalent lateral force, 200
 modal response spectrum analysis, 200
 notes, 204
 period of vibration, 201–204, 206f

Seismic design for vessels
 on braced legs, 217–223
 on conical skirt, 248–252
 design response spectrum, 208f
 general, 204–205
 on lugs, 229–239
 on rings, 223–229
 risk category, 207t
 site classification, 207t
 site coefficient, 207t
 on skirts, 239–247
 on unbraced legs, 208
 vibration periods, 206f

Self energized gaskets, 505

Self sealing closures
 with non-yielding gaskets, 505
 with yielding gaskets, 504

Self-energized gaskets *see* O-Rings

Service considerations, 33

Service failure, 7–8

Shackles, steel, 715t

Shear band, 252

Shear loads, in bolted connections, 584–585
 Shear stress, intermediate heads and, 75

Shear stress
 buckling of thin wall cylindrical shells,
 96
 at internal or external pressure on ring
 section, 52–53

Shells
 longitudinal, in shell due to shear band,
 252
 shipping saddles
see also Transportation, shipping saddles
 thickness, required, 40f

Shell design, 496–502
 high pressure design, safety factors for,
 496–497
 thick walled cylinders, 497–502,
 498f–502f

- Shell stresses due to loadings at support
 - beam locations, 316
 - equations, 316
 - nomenclature, 316
- Shell thickness procedures, 616–617
- Shifted neutral axis method, 281–291
- Shims, 590–591
- Shipping saddle, 558
 - calculation, 585
 - example, 586
 - notes, 586–594
 - tension band notation, 585
- Shipping weight, 102
- Shrink ring, 482, 518, 521f, 524f, 525f
- Side catalyst dump nozzles, dimensions and weights of, 119f
- Sign convention, 439–440
- Simplified cycle counting procedure, for fatigue analysis, 16
- Simplified elastic-plastic method, 21
- Skirt supports, 186
 - see also* Base details for vertical vessels, design of
 - crippling, 684
- Skirts, design of, 684
- Skirts, seismic design for
 - conical skirt, 248–252, 253f
 - dimensional data, 240f
 - longitudinal stresses, 246–247
 - nonuniform vessels, 240–245
 - notation, 239
 - uniform vessels, 239
- Sleeve nuts, 546
- Slenderness ratio method, 29
 - Spheres, external pressure design for, 45f, 47–48
- Slip-on flange design, 152f, 155f
- Soleplates, 590
- Solution Annealing, 740
- Spalling, 408
- Sparger details, 361f
- Spheres, field-fabricated, 594–630
 - accessories, 595
 - codes of construction, 594
 - combined girder-shell section, dimensional data for, 612
 - conversion factors, 596
 - data sheet, 604f
 - dimensional data, 597, 608
 - fabrication methods, 595
 - field hydrotests, 595
 - formulas, 596
 - heat treatment, 595
 - leg and brace dimensions, 608
 - leg attachment, 597
 - liquid levels, 597
 - materials of construction, 594–595
 - nomenclature, 605
 - notation, 596
 - notes, 595–596
 - products stored, 594
 - shell section, properties of, 611
 - sizes, thicknesses and capacity range, 595
 - supports for, 595
 - types of, 599
 - weights, 601t, 602f, 603f
- Spherical shells
 - formula, 38
- Spherical shells, stress in, 465–471
 - calculation steps, 465
 - formulas, 471
 - notation, 465
 - notes, 471
 - stress indices, loads, and geometric parameters, 471
- Spherically dished covers, 165
- Spheroidization, 740
- Spiral baffle, jacket with, 124
- Spiral pipe coil welded to shell, 124
 - half, 124–125
- Spiral weld, 762
- Splice connection, designing, 321–325
- Spray headers, 365f
- Square platforms, 571–575
- Stabilizing treatment, 740
- Stacks, vibration, 418–427
- Stainless steel sheet, weights of, 422t
- Static deflection, 420
- Steady loads, 9
- Steady state creep, 25
- Steels, 720–721
- Step cooling, 741
- Stiffeners
 - combining vacuum with other types, 42–43
 - composite, 381, 388t
 - external ring, 52
 - geometry, 51f
 - internal ring, 53
 - location of, 42–43
 - moment of inertia of bar, 49t
 - moment of inertia of composite, 50t
- Stiffening rings, 51–54
 - check for external pressure, 51t
 - dimensions, 51f, 52f
 - horizontal vessels, 52–53
 - lateral buckling of, 51–52
 - moment coefficients for base, 686t
 - moment of inertia of, 50
 - nomenclature, 51
 - partial, 446–448
 - properties of, 51–54
 - sample problem given, 53–54
 - section, shell stresses due to internal or external pressure on, 52–53
 - shell influence with, formula derivation for, 51
 - size base, 685
- Stiffeners, properties of, 614
- Strain hardening, 763
- Strain, high, 8
- Strains/fiber elongation, forming, 134–136
 - formed heads, blank diameter for, 134–136
 - nomenclature, 134
 - notes, 136
 - pipe bends, wall thinning of, 134
- Stress
 - allowable, 772–774
 - analysis, 2–3
 - categories of, 11–13
 - circumferential/latitudinal, 3
 - combined, 616
 - corrosion, 8
 - due to banding, 799–800
 - due to offset, 799–800
 - due to out of tolerance condition, 799
 - due to peaking, 799–800
 - in flat heads, 80, 82
 - formula factors, 81, 149–150
 - in heads due to internal pressure, 70–73
 - intensity, 6–7
 - limits of, 13
 - longitudinal/meridional, 3
 - radial, 3
 - redistribution, 9
 - relief, 740
 - in shell, 539–540
 - types of, 11
- Stress theories
 - comparison of, 5–7
 - maximum, 4
 - maximum shear, 4–5
- Struts, 591
- Stud tensioners, 171
- Studding flanges, 176–177
 - dimensions of, 177
 - nomenclature, 177
 - worksheet for, 177–180, 178f
- Studding outlet, 172, 175
- Studs, 546
 - pretightening methods, 546–547
- Sub-critical anneal, 740
- Superposition, principle of, 448
- Support blocks, 319–320
 - notes, 320
 - welded integral with beam, 319–320
 - welded to top of beam, 320
- Support of internal beams
 - beams, 298–299
 - design of, 303f

- Support of internal beads (*Continued*)
 load design, 299, 302f
 nomenclature, 299–300
 procedure, 299
 ring, 306
- Support of internal beds, 298–306
 beam seat support, 298
 clip support, 298
 double beam, 301f
 forces and moments, summary of, 305t
 grating, 306
 hub ring, 298
 lattice beam, 298–299
 load on circular ring, 306
 methods of, 299
 nomenclature, 299–300
 single beam, 301f
- Supports
 base details for vertical vessels, design of, 291–292
 base plates for legs, 275–276
 for bins and elevated tanks, 593
 coils, 331
 leg, 187, 278–281
 lugs, 188
 for radial beams, 325f
 ring, 189, 298–309
 saddle, 187–188
 saddles, design of horizontal vessel on, 253–266
 saddles, design for large vessels, 267–273
 seismic design for vessels, 204–205
 seismic design for vessels on braced legs, 217–223
 seismic design for vessels on lugs, 229–239
 seismic design for vessels on rings, 223–229
 seismic design for vessels on shirts, 239–247
 seismic design for vessels on unbraced legs, 208–217
 skirt, 186
 spheres, 595
 wind design per ASCE, 189–197
see also Pipe supports
- Surge capacities, 779
- Sway bracing, 222, 615
- T**
- Tail beams, 684
- Tailing devices, 672
- Tailing lugs, 689–690
- Tanks, elevated
 dimensional data, 587f
 liquid-filled, 588
 small internal pressures, 590
 support arrangements, 592f
see also Bins
- Tanks
 underground, 428–432
- Temperature
 maximum design, 84
 operating, 84
see also Minimum design metal temperature
- Tempering, 740
- Test pressure, 762
- Test weight, 102
- Testing of pressure vessels, 732–733
 Brinell, 735–736
 hardness, 734–735
 hydrostatic, 733–734
 locations of, 735
 methods of, 735
 pneumatic, 734
 proof, 734
 quantity of, 735
 timing of, 735
- Thermal conductivity, 410
- Thermal design procedure, for jacket vessels, 125
- Thermal gradients, 13
- Thermal pre-tightening, 547
- Thermal stress ratcheting, 13, 21
- Thermal stress, 13–14
- Thick walled cylinders, 497–502
 Lamé equations, 499–502
 nomenclature, 497–502
 requirements of, 498–499
 thickness determination, worksheet for, 498f–502f
- Thinning allowance, 102, 109t, 120t, 617
- Thin-walled cylindrical shells *see* Buckling of thin-walled cylindrical shells
- Thread load distribution, 540
- Thread root tooth bending stress, 540–541
- Threaded closures, 539–545
 with Bridgman gasket, 544–545
 design procedures, 539–541
 nomenclature, 539
- Through nozzles, 181
- Tie rods, 187
- Toe angle, 573
- Tolerances, 781–784
 condition, stress due to out of, 799
 flange bolt hole orientation, 798
 for horizontal vessels, 784–786
 maximum permissible bow, 787–788
 for shape of heads, 792
 for tray support rings and downcomers, 789–791
 for trayed columns fabricated in multiple sub-assemblies, 786–787
 for trays, 789
 for vertical vessels, 781–782
- Top head lugs, 678
- Toriconical transitions, dimensional data and formulas, 67–70
 due to external pressure, 69–70
 for large end, 68–69
 for small end, 69
- Torispherical heads
 internal pressure and, 46f
 reinforcement for openings in, 85
- Torque, for sealing flanges, 169–171
- Tower
 deflection, 189–197
 dimensions of, 366
 nomenclature of, 366
 vibration, 418–427
- Transcrystalline, 24
- Transformation range, 740
- Transformation temperature, 740
- Transportation
 axle loads, 573
 forces, 632, 648
 with incorporation of shipping factors, 576, 578–581
 lashing, 633, 655f
 load diagrams for moments and forces, 649–650
 methods, 634
 organizations involved in, 633
 site descriptions, 717t
 stresses, checking, 659f
 stresses, determining, 633
 uniform load case, 576, 578–581
 vertical vessel on two saddles, 576, 578–581
- Transportation, barge
 directions of ship motions, 643f
 forces, 641t
 pitch and roll, 642–643
- Transportation, rail
 bolster loads, 639f, 640f
 capacity ratios for loads, 638f
 clearances, 637f
 forces on, 643
 multiple car loading details, 637f
 special factors, 633–634
 types of cars, 636f
- Transportation, shipping saddles
 construction methods, 653f, 654f
 guidelines for, 632–633
 tension bands on, 656–657
- Transportation, truck
 examples of, 647f
 forces on, 644f

- Transporter stability, 573
 Tray support rings, tolerances for, 789–791
 Tray supports, weights of, 109t
 Trayed columns fabricated in multiple sub-assemblies, tolerances for, 786–787
 Tray nomenclature, 366–367
 Trays, 366–374
 assembly of, 370f
 nomenclature of, 366–367
 plates, 371–374
 tolerances for, 789
 tower dimensions of, 366–368
 types of, 367
 Tray types, 367
 Triaxial states of stress, 4–5
 Trunnions, 664
 design of, 706–709
 loads, 710
 tailing, 672
 Turbines, 346
 Turnbuckles, 187
 2/3 rule, 257
- U**
- Ultrasonic examination, 737–738
 Unbraced legs, seismic design for *see* Legs, seismic design for unbraced
 Underground tanks and vessels, 428–432
 anchor strap, 430
 buried vessels, 429–430
 example, 431
 external pressure, 430
 nomenclature, 428
 notes, 431–432
 in pit, 430–431
 saddle design, 430
 Unstiffened shells, maximum length of, 48t
 User's design specification, 34–35
- V**
- Vacuum chart method, 56t
 Valve trays, weights of, 109t
 Vertical vessels
 anchor bolts for, 293
 platforms for, 571f
 tolerances for, 781–782
 see also Base details for vertical vessels, design of
 Vessel proportions
 calculating, 96–99
 volumes and surface areas, 749–755
 Vessels
 classification of, 755
 parts of, 755–760
 in pit, 430–431
 types of, 755
 underground, 428–432
 vessel definition, 87f
 vessel nomenclature, 428
 Vibration, towers and stacks and, 418–427
 Vickers pyramid hardness testing, 736
 Volumes and surface areas, 749–755
 Vortex shedding, 418
 design modifications to eliminate, 419
- W**
- Washers, 546
 Water calorimeter, 410
 Weights
 allowance for plate overages, 102
 of bolts, alloy stud, 111t
 of carbon steel plate and stainless steel sheet, 105t
 estimating, 102
 of flanges, 106t, 113f
 formulas for, 103t, 104f
 of nozzles and manways, 108t
 of pipes, 110t
 of saddles and baseplates, 112t
 thinning allowance, 109t
 of tray supports and downcomer bars, 109t
 of valve trays, 109t
 of weld neck flange, 104f
 Weights, types of
 empty, 102
 erection, 102
 fabricated, 102
 operating, 102
 shipping, 102
 test, 102
 Weirs, flow over, 375
 Weld neck (integral) flanges, 74f, 104f
 Weld neck flange design, 151f
 Welding
 checking, 692–693
 leg supports, 187
 lug, 692–693
 pad eye, 693
 re-pad, 693
 saddle supports, 188
 skirt supports, 186
 Wind design per ASCE, 189–197
 ASCE/SEI 7-10, 190
 design procedure, 190
 exposure categories, 193
 gust factor, determining, 191
 notation, 189–190
 notes, 193–197
 sample problem, 191–192
 Wind velocity, critical, 418–420
 Wire wound, 475
 Wire wrapped thick-walled pressure vessel, 476
 WRC Bulletin 107, 188, 436
 WRC Bulletin 198, 448
- X**
- X-ray, requirements for, 732
- Y**
- Yield criteria *see* Stress theories
- Z**
- Zick, L. P., 187
 Zick's analysis, 187–188, 430, 633
 Zick's stresses, 187–188
 Zorilla method, 424–425